

# Uni-3 Series

PRICE COMPUTING  
ELECTRONIC SYSTEM  
SCALE PRINTER



L2 Bench Model

 **ISHIDA**

**desna**

# Uni-3 PRICE COMPUTING ELECTRONIC SYSTEM SCALE PRINTER

Customer Display



## Extraordinary Power. Exceptional Value.

With premium-class presets, fast print speed, and more labeling functions, you are getting more flexibility and more features – all for less cost than comparable price computing scales with printers.

### Three Configurations

With three models and two display types, you can easily find a Uni-3 to fit your specific application needs.

### Two Communication Choices

Ethernet or optional wireless communication enables any Uni-3 to be added to your existing network – ensuring you have consistent control of all scales in your store.



### ScaleLink Pro 5 Lite

Product management software ensures easy file maintenance as well as PLU and tare weight consistency throughout your operation.

### Flexible Presets

The power of the Uni-3 is at your fingertips with flexible preset buttons to represent PLUs, container tare values, label formats, images, and logos.

### Two Display Types

The Uni-3 L1 model features a vibrant blue alphanumeric display with a sharp white 16-segment capability. The Uni-3 L2 model features a clear alphanumeric LCD display with one line alphanumeric and one line numeric only. Each model offers a matching customer display.



Uni-3L1



Uni-3L2

### Standard Features

- Dual-range weighing
- Static TCP/IP Ethernet communication
- 2 MB standard memory
- Up to 168 function keys assist with intuitive operation
- Fast printing speed
- Meat nutrition labeling
- Multiple label formats for multi-department support
- Powerful batch printing feature
- Flash ROM for remote update of application software
- Proportional tare
- Side-load labels
- Compatible with third-party communication software, including ADC's InterScale and Invatron's PLUM



### Options/Accessories

- Wireless communication, 802.11 b/g
- SLP-5 and SLP-5 Lite scale management software, including label design, data backup and remote diagnostics
- Produce platter or fish platter

### Specifications

<b>Capacity:</b>	15lb x 0.005lb/15-30lb x 0.01lb   6kg x 2g/6-15kg x 5g Single Range: 60lb x 0.02lb/30kg x 10g
<b>Weighing resolution:</b>	3,000 display divisions maximum
<b>Display types:</b>	<b>LCD, blue, alphanumeric:</b> L1 (23 digits 16 seg) <b>LCD, backlit, alphanumeric:</b> L2 (192 x 16 dot matrix + 23 digits 7 seg)
<b>Display items:</b>	<b>Tare:</b> four digits <b>Unit price:</b> five digits <b>Total price:</b> six digits
<b>Preset keys:</b>	<b>Pole model:</b> 84 one-touch preset keys 168 presets (assign two items/key) <b>Hanging model:</b> 94 one-touch preset keys 188 presets (assign two tare/key)
<b>Platter:</b>	<b>Countertop models:</b> 14.5 in x 10.5 in <b>Hanging model:</b> 14.1 in diameter
<b>Memory capacity:</b>	2 MB
<b>Communication:</b>	TCP/IP 10/100 Base T Ethernet
<b>Printing speed:</b>	3.9 in (100 mm) per second
<b>Label:</b>	<b>Width:</b> 1.5 in-2.5 in (38 mm-64 mm) <b>Length:</b> 1.2 in-6.9 in (30 mm-175 mm)
<b>Label roll:</b>	<b>Inside diameter:</b> 1.6 in (40 mm) <b>Outside diameter:</b> 3.9 in (100 mm)
<b>Label backing paper:</b>	Width: up to 2.6 in (66 mm)
<b>Power supply:</b>	AC 100V/120V/220V/240V, 50/60Hz
<b>Power consumption:</b>	<b>Stand-by:</b> 50W. <b>In operation:</b> 100W
<b>Classification:</b>	NTEP CC 07-005
<b>Warranty:</b>	One-year limited warranty
<b>Printing:</b>	Direct thermal
<b>Thermal head:</b>	2.2 in (56 mm) (448 dot, 8 dot/mm)

### Approvals



Sales & Service:



**DESNA CONTROLS & WEIGHING INC.**  
412 Manitou Road SE, Calgary, AB T2G 4C4  
Phone: 403-243-4848 sales@desnacontrols.com  
www.desnacontrols.com